ActiveBarcode

How to use barcodes in Delphi

Version 4.x, 7.x

1

You can use ActiveBarcode in Delphi like any other control (e.g. like a button). First you have to add the ActiveBarcode control into the Delphi development environment. Go to the menu "Component" and select the function "Import ActiveX control":



2

A dialog shows up on your screen. Select "ActiveBarcode" from that list of controls. Then click the "Install..." button:

ActiveBarcode (Version 1.0) C:\Program Files\ActiveBarcode\ActiveBarcode.ocx Add. Qlass names: TBarcode Palette page: ActiveX	Remove
C:\Program Files\ActiveBarcode\ActiveBarcode.ocx Add. Class names: TBarcode Palette page: ActiveX	<u>R</u> emove
C:\Program Files\ActiveBarcode\ActiveBarcode.ocx Add. Class names: TBarcode Palette page: ActiveX	Femove
C:\Program Files\ActiveBarcode\ActiveBarcode.ocx Add. Class names: TBarcode Palette page: ActiveX	<u>R</u> emove
Add Class names: TBarcode Palette page: ActiveX	<u>R</u> emove
Class names: TBarcode Palette page: ActiveX	^
Palette page: ActiveX 💌	
Palette page: ActiveX 💌	-
Unit dir name: C:\Program Files\Borland\Delphi4\Impor	s
Searchpath: \$(DELPHI)\Lib;\$(DELPHI)\Bin;\$(DELPH)\Imports
	JAImports

Follow the instructions showing on your screen.

Now the ActiveBarcode control is added to your Delphi development environment. The barcode icons of ActiveBarcode will appear in the tool bar located in "ActiveX":



4

Now select this icon and place it anywhere in a form. The barcode control will be placed in that form. This will be a standard barcode. You can change this and all other properties of that barcode control in the "Object Inspector".

		Object Inspecto	or
		Barcode1: TBar	code
		Properties Events	
		Picture	(TOleGraphic
		PopupMenu	
12345678	190	PrintFix	False
12010010		Rotate	0
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	ShowHint	False
		ShowText	True
		TabOrder	0
		TabStop	True
		Tag	0
		Text	1234567 20 ;
		Тор	32

3

5

For example you can select any barcode that is supported by ActiveBarcode: QR Code, GS1/EAN-128, Data Matrix, GTIN/EAN-13, Code 39, Code 93, GS1-Data Matrix, Code 128, PDF417, DUN-14, EAN-8, EAN-14, EAN-18, ISBN, ITF-14, NVE, PZN8, SCC-14, SSCC-18, ...

Programming:

To set the properties is very simple. Some examples:

Barcode1.Text := '123456789012'; Barcode1.BackColor := clWhite; Barcode1.ForeColor := clBlack;

Using the Picture Property:

How to copy the barcode image into a image object:

Image1.Picture.Bitmap.Height := Barcode1.Height; Image1.Picture.Bitmap.Width := Barcode1.Width; Barcode1.Picture.CleanupInstance; Image1.Picture.Bitmap.Canvas.Draw(0,0,Barcode1.Picture.graphic);

Clipboard:

How to copy a barcode into the Windows clipboard. First as meta file (WMF):

Barcode1.CopyToClipboard;

And now as bitmap image:

Image1.Picture.Bitmap.Height := Barcode1.Height; Image1.Picture.Bitmap.Width := Barcode1.Width; Barcode1.Picture.PictureAdapter := nil; // delphi workaround Barcode1.Picture.CleanupInstance; Clipboard.Assign(Image1.Picture.Bitmap);

Copyright © 1994-2025 Frank Horn & Lars Schenk All trademarks and product names mentioned are the property of their respective owners.